

This table is recommended for development planning and control use.

Table 4 – Hazard to People Classification using Hazard Rating ($HR = d \times (v + 0.5) + DF$) for (Source Table 13.1 of FD2320/TR2 - Extended version)

HR	Depth of flooding - d (m)												
	DF = 0.5				DF = 1								
Velocity v (m/s)	0.05	0.10	0.20	0.25	0.30	0.40	0.50	0.60	0.80	1.00	1.50	2.00	2.50
0.0	0.03+0.5 = 0.53	0.05+0.5 = 0.55	0.10+0.5 = 0.60	0.13+0.5 = 0.63	0.15+1.0 = 1.15	0.20+1.0 = 1.20	0.25+1.0 = 1.25	0.30+1.0 = 1.30	0.40+1.0 = 1.40	0.50+1.0 = 1.50	0.75+1.0 = 1.75	1.00+1.0 = 2.00	1.25+1.0 = 2.25
0.1	0.03+0.5 = 0.53	0.06+0.5 = 0.56	0.12+0.5 = 0.62	0.15+0.5 = 0.65	0.18+1.0 = 1.18	0.24+1.0 = 1.24	0.30+1.0 = 1.30	0.36+1.0 = 1.36	0.48+1.0 = 1.48	0.60+1.0 = 1.60	0.90+1.0 = 1.90	1.20+1.0 = 2.20	1.50+1.0 = 2.55
0.3	0.04+0.5 = 0.54	0.08+0.5 = 0.58	0.15+0.5 = 0.65	0.19+0.5 = 0.69	0.23+1.0 = 1.23	0.30+1.0 = 1.30	0.38+1.0 = 1.38	0.45+1.0 = 1.45	0.60+1.0 = 1.60	0.75+1.0 = 1.75	1.13+1.0 = 2.13	1.50+1.0 = 2.50	1.88+1.0 = 2.88
0.5	0.05+0.5 = 0.55	0.10+0.5 = 0.60	0.20+0.5 = 0.70	0.25+0.5 = 0.75	0.30+1.0 = 1.30	0.40+1.0 = 1.40	0.50+1.0 = 1.50	0.60+1.0 = 1.60	0.80+1.0 = 1.80	1.00+1.0 = 2.00	1.50+1.0 = 2.50	2.00+1.0 = 3.00	2.50+1.0 = 3.50
1.0	0.08+0.5 = 0.58	0.15+0.5 = 0.65	0.30+0.5 = 0.80	0.38+0.5 = 0.88	0.45+1.0 = 1.45	0.60+1.0 = 1.60	0.75+1.0 = 1.75	0.90+1.0 = 1.90	1.20+1.0 = 2.20	1.50+1.0 = 2.50	2.25+1.0 = 3.25	3.00+1.0 = 4.00	3.75+1.0 = 4.75
1.5	0.10+0.5 = 0.60	0.20+0.5 = 0.70	0.40+0.5 = 0.90	0.50+0.5 = 1.00	0.60+1.0 = 1.60	0.80+1.0 = 1.80	1.00+1.0 = 2.00	1.20+1.0 = 2.20	1.60+1.0 = 2.60	2.00+1.0 = 3.00	3.00+1.0 = 4.00	4.00+1.0 = 5.00	5.00+1.0 = 6.00
2.0	0.13+0.5 = 0.63	0.25+0.5 = 0.75	0.50+0.5 = 1.00	0.63+0.5 = 1.13	0.75+1.0 = 1.75	1.00+1.0 = 2.00	1.25+1.0 = 2.25	1.50+1.0 = 2.50	2.00+1.0 = 3.00	3.50	4.75	6.00	7.25
2.5	0.15+0.5 = 0.65	0.30+0.5 = 0.80	0.60+0.5 = 1.10	0.75+0.5 = 1.25	0.90+1.0 = 1.90	1.20+1.0 = 2.20	1.50+1.0 = 2.50	1.80+1.0 = 2.80	3.40	4.00	5.50	7.00	8.50
3.0	0.18+0.5 = 0.68	0.35+0.5 = 0.85	0.70+0.5 = 1.20	0.88+0.5 = 1.38	1.05+1.0 = 2.05	1.40+1.0 = 2.40	1.75+1.0 = 2.75	3.10	3.80	4.50	6.25	8.00	9.75
3.5	0.20+0.5 = 0.70	0.40+0.5 = 0.90	0.80+0.5 = 1.30	1.00+0.5 = 1.50	1.20+1.0 = 2.20	1.60+1.0 = 2.60	3.00	3.40	4.20	5.00	7.00	9.00	11.00
4.0	0.23+0.5 = 0.73	0.45+0.5 = 0.95	0.90+0.5 = 1.40	1.13+0.5 = 1.63	1.35+1.0 = 2.35	1.80+1.0 = 2.80	3.25	3.70	4.60	5.50	7.75	10.00	12.25
4.5	0.25+0.5 = 0.75	0.50+0.5 = 1.00	1.00+0.5 = 1.50	1.25+0.5 = 1.75	1.50+1.0 = 2.50	2.00+1.0 = 3.00	3.50	4.00	5.00	6.00	8.50	11.00	13.50
5.0	0.28+0.5 = 0.78	0.60+0.5 = 1.10	1.10+0.5 = 1.60	1.38+0.5 = 1.88	1.65+1.0 = 2.65	3.20	3.75	4.30	5.40	6.50	9.25	12.00	14.75

Flood Hazard Rating (HR)	Colour Code	Hazard to People Classification
Less than 0.75		Very low hazard - Caution
0.75 to 1.25		Danger for some – includes children, the elderly and the infirm
1.25 to 2.0		Danger for most – includes the general public
More than 2.0		Danger for all – includes the emergency services